WireFree Zigbee

The smart, wirefree dual shaft motor, specifically designed to tilt and lift small and medium interior venetian, roman and pleated applications.



PRODUCTS MAIN FUNCTIONALITIES



Zigbee 3.0Ri-directional feed

Bi-directional feedback through TaHoma by Somfy app



Re-chargeable external battery pack



Adjustable tilting and lifting speed

in increments of 1rpm with TaHoma pro app



Designed for whisper quiet operation



Soft-start and soft-stop



Simple, quick and errorfree commissioning through TaHoma pro app



'my' favourite position



USB-C fast charge

Charges external battery in 1h 40min using the Somfy charger



Solar charging options



Openness of the Zigbee protocol



Battery level and position feedback



Compatible with TaHoma switch



Magnetic charging option



Direct power option



COMPATIBLE END PRODUCTS











Tilt & Lift 25 Zigbee WireFree Zigbee

Sheer Blinds

Roman Blinds

Pleated & Cellular

7ehra Blinds

Venetian

Blinds

BENEFITS FOR END USERS

Robust and easy:

- Bi-directional feedback (know the motors position and
- battery level) anytime, anywhere.
- · No wiring; no electrician required.
- Optional constant, direct power option using 12V DC

Convenient and smart:

- Precise tilting control with Ysia 5 Variation [1871281]². Designed for silence, seamless operation.
- Precision percentage blind control with TaHoma switch.
- USB-C Fast charge for optimised charging experience.
- Magnetic Charging accessories available².
- Compatible with the Zigbee WireFree Solar Panel¹.
- Compatible with TaHoma switch, Apple HomeKit and other Zigbee 3.0 devices thanks to TaHoma switch.

BENEFITS FOR PROFESSIONALS

Easy Installation:

- Suitable for headrails of at least 25 x 25mm with standard CTS25 accessories.
- No electrician required powered either through an external rechargeable li-ion battery or a direct 12V DC power supply.
- Adjustable tilting and lifting speed in increments of 1rpm through the TaHoma pro application.

Easy programming and adjustment with TaHoma® pro:

- Installation and programming done directly from the app: including intuitive step-by-step programming instructions.
- Dedicated after sales and remote maintenance tool, Serv-e-Go1.

Reliability:

| Highly secure protocol |
|--|
| Somfy Quality and Warranty |

TECHNICAL DATA

| Voltage Supply | 12V DC | |
|------------------------------|--|--|
| Index Protection Rating | IP20 (for indoor use only) | |
| Limit Switch Type | Electronic | |
| Temperature Working Range | 0°C to 60°C | |
| Temperature Storage Range | -20°C to 60°C | |
| Insulation Class | Class III | |
| Antenna | 12 cm wire length. Must not be cut or lengthened. For greatest RF range, it must not be exposed and should not come in to contact with metal surfaces. RF wire may need to be repositioned for optimal performance. Keep out of the rail/tube/headrail/cassette. | |

PERFORMANCE

| Nominal Torque | 0.8Nm |
|----------------------------|---|
| Nominal Speed | Lifting: 30 rpm Tilting: 18 rpm |
| Adjustable Speed | Lifting: 18 - 30 rpm Tilting: 10 — 20 rpm (increments of 1rpm using TaHoma pro app) |
| Sound Level | 46 dBA (at nominal speed) |
| Radio Protocol | Zigbee 3.0/Bluetooth 4.2 (with TaHoma Pro) |
| Radio Range | 7m [in room; extendable with Zigbee repeaters] |
| Radio Frequency | 2.4 GHz |
| Direct Power Option | 9028893 — 12V AC/DC Power Supply ² |
| External Battery Option | 9028930 — External Li-ion Battery Pack² |
| Battery Lifetime | 10 months³ (external battery pack) |
| Low Battery Indicator | LED on external battery pack |
| Charging Time | 1hr 45m (with 9028922) |
| Motor Item Number | 1241674 |





MOTOR DIMENSIONS

Motor Length (L) 197mm without accessories [207mm with accessories]

Head diameter Ø (D) 40mm

Min Headrail Size 25 x 25mm with standard CTS2 Somfy Accessories

Tilt & Lift 25 ZigbeeWireFree Zigbee

MOTOR CABLE TYPE:

Adhesive strip, mounting clips and screws



Battery Length (L) 300mm

Battery Width (W) 23mm

Battery Height (H) 25mm

Battery Mounting



WIREFREE ELECTRONICS AND ACCESSORIES (each product sold separately)

Power Supply, Charging and Electronics:

| 9028893 | 12V AC/DC Power Supply for WireFree Range (RTS & Zigbee) | Direct Fixed power option | |
|---------|--|---|--|
| 9028930 | External Li-ion Battery Pack | | |
| 9028922 | Zigbee Li-ion USB C Charger | C. Assert I Debberon and I assert a street | |
| 9028564 | Magnetic Adaptor for Zigbee USB C Charger | | |
| 9028563 | Magnetic Rigid Cable for Zigbee USB C Charger | External Battery pack power option mester 2, 2024) | |
| 9028565 | USB C Zigbee 20cm Charging Extension Cable | | |
| 9029114 | WireFree Li-ion Zigbee Solar Panel (available from Semester 2, 2024) | | |

Accessories available:

9162143

| BEARINGS: | | SHAFT ADAPTERS: | |
|--------------------|--|----------------------|----------------------------------|
| 9162175 | BEARING CTS25 VERSARAIL EASY UP | 9163251 | SHAFT ADAPTER HEXAGONAL 5mm |
| 9162176 | BEARING CTS 25 HD ULTIMATE | 9163253 | SHAFT ADAPTER SQUARE 5mm |
| 9162139 | BEARING CTS 25 FABER MINIMATIC / SOFTLINE | 9163252 | SHAFT ADAPTER HEXAGONAL 6mm |
| HEADRAIL ADAPTERS: | | 9163254 | LONG SHAFT ADAPTER HEXAGONAL 5mm |
| | | 9163256 | LONG SHAFT ADAPTER SQUARE 5mm |
| 9163260 | HEADRAIL ADAPTER HD ULTIMATE | 9163255 | LONG SHAFT ADAPTER HEXAGONAL 6mm |
| 9163261 9163262 | HEADRAIL ADAPTER FABER MINIMATIC HEADRAIL ADAPTER FABER SOFTLINE | CONES & CONE COVERS: | |
| 9163332 | HEADRAIL ADAPTER B.I.G | 1781003 | SHORT CONE HEXAGONAL 5 |
| 9163268 | HEADRAIL ADAPTER VEROSOL PLEATED | 1781002 | SHORT CONE HEXAGONAL 6 |
| RINGS & | RINGS & LADDER GRIP: 1781000 SHORT COVER CTS | | SHORT COVER CTS |
| 9162257 | STOP RING 6mm HEX/5mm SQUARE SHAFT | 9162137 | CONE 25/35 - HEXA 6mm |
| 9163292 | LADDER GRIP - LADDER BRAID LOOP | 9162138 | CONE 25/35 SQUARE 5mm |
| 9162141 | RING 25/35 HEXAGONAL 5mm | 9162140 | COVER CTS 25/35 |
| 9162142 | RING 25/35 HEXAGONAL 6mm | - | |



RING 25/35 SQUARE 5mm